

# Material Safety Data Sheet

Issue Date: 3/8/2007

Page 1 of 3

## Section 1: Chemical Product and Company Identification

Cat#: 03326

Part Name: POLYACRYLIC ACID, 25% SOLIDS IN WATER Mw > 200,000

Supplier: Polysciences, Inc.  
400 Valley Road  
Warrington, PA 18976  
Telephone #215-343-6484

## Section 2: Composition/ Information on Ingredients

Item#	Name	CAS#	% in product
1	2-Propenoic acid, homopolymer	009003014	19
2	Poly(acrylic acid) sodium salt	009003047	6
3	Water	007732185	75

## OSHA (ACGIH) Exposure Limits

CAS#	Name	TWA		STEL		CEILING	
		ppm	mg/	ppm	mg/m3	ppm	mg/m3
CAS#: 007732185	IDLH: NE						
OSHA		NE	NE	NE	NE	NE	NE
ACGIH		NE	NE	NE	NE	NE	NE
CAS#: 009003014	IDLH: NE						
OSHA		NE	NE	NE	NE	NE	NE
ACGIH		NE	NE	NE	NE	NE	NE
CAS#: 009003047	IDLH: NE						
OSHA		NE	NE	NE	NE	NE	NE
ACGIH		NE	NE	NE	NE	NE	NE

## Section 3: Hazards Identification

Low hazard for usual industrial or commercial handling.

Hazard Ratings:

These ratings are Polysciences' Inc. own assessments of the properties of the material using the ANSI/NFPA 704 Standard. Additional information can be found by consulting in the NFPA published ratings lists (List 325 and List 49).

If no data is listed the information is not available.

Health	Flammability	Reactivity
1	0	0

## Section 4: First Aid Measures

Flush eyes with flowing water for at least 15 minutes.

If breathing is difficult, contact emergency personnel.

If swallowed, NO NOT INDUCE vomiting. Give 8 oz. of water or milk to drink. Call a physician or the POISON CONTROL CENTER immediately. Never give anything by mouth to an unconscious person.

Remove to fresh air.

Wash skin with deluge of water for at least 15 minutes.

## Section 5: Fire Fighting Measures

Flash point, deg F.: no data

Method: no data

UEL: no data LEL: no data

Autoignition temperature, deg. F.: no data

Flammability Classification: no data

Flame Propagation Rate: no data

Hazardous Combustion Products: no data

## Section 6: Accidental Release Measures

Any information listed below is to be considered in addition to internal guidelines for isolation of spill, containment of spill, removal of ignition sources from immediate area, and collection for disposal of spill by trained, properly protected clean up personnel.

Absorb liquids on absorbent material.

Contain spilled liquids.

Protect personnel from exposure.

## Section 7: Handling and Storage

Store at room temp