

SECTION 1: Identification

1.1. Identification

Product form	: Mixture
Trade name	: CMCP-9 Low viscosity mountant
Product code	: 16299
Formula	: mixture

1.2. Recommended use and restrictions on use

Recommended use	: Use as laboratory reagent, Manufacture of substances
-----------------	--

1.3. Supplier

Supplier

Polysciences
400 Valley Road
Warrington, PA 18976 - United States
T +1 215 343 6484 - F +1 215 343 0214
info@polysciences.com - www.polysciences.com

1.4. Emergency telephone number

Emergency number	: 24-hour emergency phone number ChemTel 1-800-255-3924
------------------	---

SECTION 2: Hazard(s) identification


2.1. Classification of the substance or mixture

GHS US classification

Acute toxicity (oral) Category 4	Harmful if swallowed
Acute toxicity (inhalation) Category 3	Toxic if inhaled
Skin corrosion/irritation Category 1C	Causes severe skin burns and eye damage
Serious eye damage/eye irritation Category 2B	Causes eye irritation

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)	: 
Signal word (GHS US)	: Danger
Hazard statements (GHS US)	: Harmful if swallowed Causes severe skin burns and eye damage Causes eye irritation Toxic if inhaled
Precautionary statements (GHS US)	: Do not breathe dust/fume/gas/mist/vapors/spray. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash hands, forearms and face thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

CMCP-9 Low viscosity mountant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Water	(CAS-No.) 7732-18-5	51 – 60.5	Not classified
DL-Lactic Acid	(CAS-No.) 50-21-5	21 – 30	Skin Corr. 1C, H314 Eye Dam. 1, H318 Eye Irrit. 2B, H320
Phenol Liquified 90%	(CAS-No.) 108-95-2	21 – 30	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Corr. 1B, H314 Muta. 2, H341 STOT RE 2, H373
Polyvinyl alcohol	(CAS-No.) 9002-89-5	0 – 5	Not classified

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Call a physician immediately.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a physician immediately. Call a doctor.
- First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
- First-aid measures after ingestion : Rinse mouth. Call a physician immediately. Do not induce vomiting.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after skin contact : Burns. Irritation.
- Symptoms/effects after eye contact : Serious damage to eyes. Mild eye irritation.
- Symptoms/effects after ingestion : Burns.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

- Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes. Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

CMCP-9 Low viscosity mountant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Wear personal protective equipment.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store at room temp. Store locked up. Store in a well-ventilated place. Keep cool. Keep container tightly closed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

CMCP-9 Low viscosity mountant
No additional information available
Phenol Liquified 90% (108-95-2)
No additional information available
DL-Lactic Acid (50-21-5)
No additional information available
Water (7732-18-5)
No additional information available
Polyvinyl alcohol (9002-89-5)
No additional information available

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : viscous liquid phenol odor.

CMCP-9 Low viscosity mountant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Color	: No data available
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: >
Flash point	: no data
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: no data
Relative vapor density at 20°C	: no data
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Toxic if inhaled.

ATE US (oral)	500 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h

DL-Lactic Acid (50-21-5)	
LD50 oral rat	3543 mg/kg
LD50 dermal rabbit	> 2000 mg/kg body weight Animal: rabbit, Guideline: EPA OPP 81-2 (Acute Dermal Toxicity)

CMCP-9 Low viscosity mountant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DL-Lactic Acid (50-21-5)	
LC50 Inhalation - Rat	> 7.94 mg/l/4h

Polyvinyl alcohol (9002-89-5)	
LD50 oral rat	> 5000 mg/kg
LC50 Inhalation - Rat	> 24 mg/l

Skin corrosion/irritation	: Causes severe skin burns.
Serious eye damage/irritation	: Causes eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Phenol Liquified 90% (108-95-2)	
IARC group	3 - Not classifiable

Polyvinyl alcohol (9002-89-5)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Phenol Liquified 90% (108-95-2)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after skin contact	: Burns. Irritation.
Symptoms/effects after eye contact	: Serious damage to eyes. Mild eye irritation.
Symptoms/effects after ingestion	: Burns.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects. Before neutralisation, the product may represent a danger to aquatic organisms.

DL-Lactic Acid (50-21-5)	
LC50 fish 1	195 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 Daphnia 1	130 mg/l Test organisms (species): Daphnia magna

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

CMCP-9 Low viscosity mountant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN2821 Phenol solutions, 6.1, II
UN-No.(DOT) : UN2821
Proper Shipping Name (DOT) : Phenol solutions
Class (DOT) : 6.1 - Class 6.1 - Poisonous materials 49 CFR 173.132
Packing group (DOT) : II - Medium Danger
Hazard labels (DOT) : 6.1 - Poison



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 243
DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)
TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.
DOT Packaging Exceptions (49 CFR 173.xxx) : 153
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Emergency Response Guide (ERG) Number : 153
Other information : No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

Transport document description (IMDG) : UN 2821 PHENOL SOLUTION, 6.1, II
UN-No. (IMDG) : 2821
Proper Shipping Name (IMDG) : PHENOL SOLUTION
Class (IMDG) : 6.1 - Toxic substances
Packing group (IMDG) : II - substances presenting medium danger
Limited quantities (IMDG) : 100 ml

Air transport

Transport document description (IATA) : UN 2821 Phenol solution, 6.1, II
UN-No. (IATA) : 2821

CMCP-9 Low viscosity mountant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name (IATA)	: Phenol solution
Class (IATA)	: 6.1 - Toxic Substances
Packing group (IATA)	: II - Medium danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Phenol Liquified 90% (108-95-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	1000 lb
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	10000 lb 500lb if the substance is solid in powder form with particle size less than 100 microns, or is in solution or molten form
DL-Lactic Acid (50-21-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Water (7732-18-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Polyvinyl alcohol (9002-89-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).

15.2. International regulations

CANADA

Phenol Liquified 90% (108-95-2)	
Listed on the Canadian DSL (Domestic Substances List)	
DL-Lactic Acid (50-21-5)	
Listed on the Canadian DSL (Domestic Substances List)	
Water (7732-18-5)	
Listed on the Canadian DSL (Domestic Substances List)	
Polyvinyl alcohol (9002-89-5)	
Listed on the Canadian DSL (Domestic Substances List)	

EU-Regulations

DL-Lactic Acid (50-21-5)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

National regulations

DL-Lactic Acid (50-21-5)	
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Japanese ISHL (Industrial Safety and Health Law) Listed on KECL/KECI (Korean Existing Chemicals Inventory) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on INSQ (Mexican National Inventory of Chemical Substances) Listed on CICR (Turkish Inventory and Control of Chemicals) Listed on the TCSI (Taiwan Chemical Substance Inventory)	

15.3. US State regulations

CMCP-9 Low viscosity mountant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	State or local regulations
Phenol Liquified 90%(108-95-2)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard Rating

- Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
- Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)
- Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

POLYSCIENCES, INC. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. POLYSCIENCES, INC. makes no representations or warranties, either expressed or implied of merchantability, fitness for particular purposes with respect to the information set forth herein or to which the information refers. Accordingly, POLYSCIENCES, INC. will not be responsible for damages resulting from the use of or reliance upon this information.