

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 05/27/2021 Supersedes: 05/16/2002 Version: 1.0

SECTION 1: Identification	
1.1. Identification	
Product form	: Mixture
Product name	: TDMAC HEPARIN COMPLEX 2% W/W (DS# 172)
Product code	: 03921
Formula	: mixture
1.2. Recommended use and restriction	ns on use
Recommended use	: Use as laboratory reagent, Manufacture of substances
1.3. Supplier	
Supplier Polysciences 400 Valley Road Warrington, PA 18976 - United States T +1 215 343 6484 - F +1 215 343 0214 info@polysciences.com - www.polysciences	<u>.com</u>
1.4. Emergency telephone number	
Emergency number	: 24-hour emergency phone number ChemTel 1-800-255-3924 Contract # MIS1592086
SECTION 2: Hazard(s) identificatio	
2.1. Classification of the substance or	mixture
GHS US classification	
Flammable liquids Category 2 Acute toxicity (dermal) Category 4 Skin corrosion/irritation Category 2	Highly flammable liquid and vapor Harmful in contact with skin Causes skin irritation
2.2. GHS Label elements, including pr	ecautionary statements
GHS US labeling	
Hazard pictograms (GHS US)	
Signal word (GHS US)	: Danger
Hazard statements (GHS US)	 Highly flammable liquid and vapor Harmful in contact with skin Causes skin irritation
Precautionary statements (GHS US)	 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.
2.3. Other hazards which do not result	t in classification
No additional information available	
2.4. Unknown acute toxicity (GHS US)	
Not applicable	
SECTION 3: Composition/Informat	ion on ingredients
3.1. Substances	
Not applicable	
2.2 Mixtures	

3.2. **Mixtures**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Toluene ACS	(CAS-No.) 108-88-3	41 – 50	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Naphtha (petroleum), solvent-refined light	(CAS-No.) 64741-84-0	31 – 40	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Benzene	(CAS-No.) 71-43-2	1 – 10	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Muta. 1B, H340 Carc. 1A, H350 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 3, H412
n-hexane	(CAS-No.) 110-54-3	1 – 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Cyclohexane	(CAS-No.) 110-82-7	0 – 5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Heparin, sodium salt (Sodium heparin, from porcine intestinal mucosa)	(CAS-No.) 9041-08-1	0 – 5	Not classified
Tridodecylmethylammonium chloride	(CAS-No.) 7173-54-8	0 – 5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT SE 2, H371
N-Heptane, Pure 99.0%	(CAS-No.) 142-82-5	0 – 5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Call a poison center/doctor/physician if you feel unwell.
First-aid measures after inhalation	 Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell. Rinse mouth.
4.2. Most important symptoms and effective states and effective symptometry and effective sympto	ffects (acute and delayed)
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Mild eye irritation.
4.3. Immediate medical attention and	special treatment, if necessary
Treat symptomatically.	

Safety Data Sheet

SECTION 5: Fire-fighting measures	
5.1. Suitable (and unsuitable) extinguish	hing media
Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
5.2. Specific hazards arising from the cl	hemical
Fire hazard	: Highly flammable liquid and vapor.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.
5.3. Special protective equipment and p	recautions for fire-fighters
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
SECTION 6: Accidental release mea	sures
6.1. Personal precautions, protective ec	quipment and emergency procedures
6.1.1. For non-emergency personnel	
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	
Avoid release to the environment.	
6.3. Methods and material for containme	ent and cleaning up
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.
6.4. Reference to other sections	
For further information refer to section 13.	
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse.
7.2. Conditions for safe storage, includi	ing any incompatibilities
Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store at room temp. Store in a well-ventilated place. Keep cool. Keep container tightly closed.
SECTION 8: Exposure controls/pers	sonal protection
8.1. Control parameters	
TDMAC HEPARIN COMPLEX 2% W/W (DS	# 172)
No additional information available	

Benzene (71-43-2)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (ppm)	0.5 ppm
ACGIH STEL (ppm)	2.5 ppm
ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route, Confirmed Human Carcinogen

Safety Data Sheet

USA - ACGIH - Biological Exposure Indices	
Biological Exposure Indices (BEI)	25 µg/g Kreatinin Parameter: S-Phenylmercapturic acid - Medium: urine - Sampling
biological Exposure indices (BEI)	time: end of shift (background) 500 μg/g Kreatinin Parameter: t,t-Muconic acid - Medium: urine - Sampling time: end of
	shift (background)
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) (ppm)	10 ppm 1 ppm
OSHA PEL (STEL) (ppm)	5 ppm (see 29 CFR 1910.1028)
OSHA PEL C [ppm]	25 ppm
Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	50 ppm Peak (10 minutes)
USA - IDLH - Occupational Exposure Limits	
US IDLH (ppm)	500 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA [ppm]	0.1 ppm
NIOSH REL STEL [ppm]	1 ppm
Cyclohexane (110-82-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Cyclohexane
ACGIH TWA (ppm)	100 ppm
Remark (ACGIH)	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2020
USA - OSHA - Occupational Exposure Limits	ACCI112020
Local name	Cyclohexane
OSHA PEL (TWA) (mg/m ³)	1050 mg/m ³
OSHA PEL (TWA) (ppm)	300 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
US IDLH (ppm)	1300 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA) (mg/m ³)	1050 mg/m ³
NIOSH REL TWA [ppm]	300 ppm
Heparin, sodium salt (Sodium heparin, from porc	ine intestinal mucosa) (9041-08-1)
No additional information available	
N-Heptane, Pure 99.0% (142-82-5)	
No additional information available	
n-hexane (110-54-3)	
USA - ACGIH - Occupational Exposure Limits	
Local name	n-Hexane
ACGIH TWA (ppm)	50 ppm
Remark (ACGIH)	TLV® Basis: CNS impair; peripheral neuropathy; eye irr. Notations: Skin; BEI
ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route
Regulatory reference	ACGIH 2020
USA - OSHA - Occupational Exposure Limits	
Local name	n-Hexane
OSHA PEL (TWA) (mg/m ³)	1800 mg/m ³
OSHA PEL (TWA) (mg/m)	500 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
US IDLH (ppm)	1100 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA) (mg/m ³)	180 mg/m ³
NIOSH REL (TWA) (IIIg/III-) NIOSH REL TWA [ppm]	180 mg/m ³ 50 ppm
	oo ppiii

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Naphtha (petroleum), solvent-refined light (6474	I-84-0)
No additional information available	
Toluene ACS (108-88-3)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Toluene
ACGIH TWA (ppm)	20 ppm
Remark (ACGIH)	TLV® Basis: Visual impair; female repro; pregnancy loss. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2020
USA - OSHA - Occupational Exposure Limits	
Local name	Toluene
OSHA PEL (TWA) (ppm)	200 ppm
OSHA PEL C [ppm]	300 ppm
Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	500 ppm 10 mins.
Remark (OSHA)	(2) See Table Z-2.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-2
USA - IDLH - Occupational Exposure Limits	
US IDLH (ppm)	500 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA) (mg/m ³)	375 mg/m ³
NIOSH REL TWA [ppm]	100 ppm
NIOSH REL (STEL) (mg/m ³)	560 mg/m ³
NIOSH REL STEL [ppm]	150 ppm
Tridodecylmethylammonium chloride (7173-54-8	
No additional information available	

8.2. Appropriate engineering controls

Appropriate engineering controls Environmental exposure controls

S : Ensur

: Ensure good ventilation of the work station.: Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties		
9.1. Information on basic physical and chemical properties		
Physical state	: Liquid	
Appearance	: clear colorless liquid solvent odor.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<u> </u>	
Color	: Mixture contains one or more component(s) which have the following colour(s): Colorless clear
Odor	 There may be no odour warning properties, odour is subjective and inadequate to warn o overexposure. Mixture contains one or more component(s) which have the following odour: gasoline-like liquid with gasoline-like model airplane glue petroleum
Odor threshold	: No data available
рН	: No data available
Melting point	: no data
Freezing point	: No data available
Boiling point	: 148
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: 83 mm Hg
Relative vapor density at 20 °C	: 3.28
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity			
10.1.	Reactivity		
The pro	The product is non-reactive under normal conditions of use, storage and transport. Highly flammable liquid and vapor.		

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information	on	
11.1. Information on toxicological effects		
Acute toxicity (oral)	: Not classified	
Acute toxicity (dermal)	: Harmful in contact with skin.	
Acute toxicity (inhalation)	: Not classified	
ATE US (dermal)	1100 mg/kg body weight	
Benzene (71-43-2)		
LD50 oral rat	810 mg/kg	
LD50 dermal rabbit	> 8200 mg/kg	
05/27/2021	EN (English US)	6/12

Safety Data Sheet

Benzene (71-43-2)	
LC50 Inhalation - Rat	44.66 mg/l/4h
Cyclohexane (110-82-7)	
LD50 oral rat	12705 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat [ppm]	> 9500 ppm/4h
n-hexane (110-54-3)	
LD50 oral rat	25 g/kg
LD50 dermal rabbit	3000 mg/kg
LC50 Inhalation - Rat [ppm]	48000 ppm/4h
Naphtha (petroleum), solvent-refined	light (64741-84-0)
LD50 oral rat	> 7000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat [ppm]	73680 ppm/4h
Toluene ACS (108-88-3)	
LD50 oral rat	2600 mg/kg
LD50 dermal rabbit	12000 mg/kg
LC50 Inhalation - Rat	12.5 mg/l/4h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Banzana (74.42.2)	

Benzene (71-43-2)				
IARC group 1 - Carcinogenic to humans				
National Toxicity Program (NTP) Status	Evidence of Carcinogenicity, Known Human Carcinogens			
In OSHA Hazard Communication Carcinogen list	Yes			
In OSHA Specifically Regulated Carcinogen list	Yes			

Toluene ACS (108-88-3)			
IARC group	3 - Not classifiable		
Reproductive toxicity	Not classified		

STOT-single exposure	exposure : Not classified			
Cyclohexane (110-82-7)				
STOT-single exposure May cause drowsiness or dizziness.				
N-Heptane, Pure 99.0% (142-82-5)				
STOT-single exposure May cause drowsiness or dizziness.				
n-hexane (110-54-3)				
STOT-single exposure May cause drowsiness or dizziness.				
Toluene ACS (108-88-3)				
STOT-single exposure May cause drowsiness or dizziness.				
Tridodecylmethylammonium chloride (7173-54-8)				
STOT-single exposure May cause respiratory irritation. May cause damage to organs.				
STOT-repeated exposure : Not classified				

Safety Data Sheet

12.1

Toxicity Ecology - general

Benzene (71-43-2)

LC50 fish 1 EC50 Daphnia 1

LC50 fish 2

LC50 fish 1

LC50 fish 2

LC50 fish 1

EC50 Daphnia 1

EC50 Daphnia 1

EC50 Daphnia 2

EC50 Daphnia 1

NOEC chronic algae

n-hexane (110-54-3)

Cyclohexane (110-82-7)

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Benzene (71-43-2)				
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.			
n-hexane (110-54-3)				
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.			
Toluene ACS (108-88-3)				
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.			
Aspiration hazard	: Not classified			
Viscosity, kinematic	: No data available			
Symptoms/effects after skin contact	: Irritation.			
Symptoms/effects after eye contact	: Mild eye irritation.			

effects in the environment.

0.9 mg/l

0.94 mg/l

3.88 mg/l

0.74 mg/l

: The product is not considered harmful to aquatic organisms or to cause long-term adverse

10.7 - 14.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

3.96 - 5.18 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

23.03 - 42.07 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

2.1 - 2.98 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

8.76 - 15.6 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

10 mg/l (Exposure time: 48 h - Species: Daphnia magna)

9.74 mg/l (Exposure time: 48 h - Species: Daphnia magna)

5.3 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])

NOEC chronic crustacea

Naphtha (petroleum), solvent-refined light (64741-84-0)

12.2. Persistence and degradability

No additional information available

Toluene ACS (108-88-3)

12.3. **Bioaccumulative potential**

Benzene (71-43-2)		
BCF fish 1	3.5 - 4.4	
Partition coefficient n-octanol/water (Log Pow)	2.1	
Cyclohexane (110-82-7)		
Partition coefficient n-octanol/water (Log Pow) 3.44		

Mobility in soil 12.4.

No additional information available

0 = 10 = 101		0//0
No addit	ional information available	
12.5.	Other adverse effects	

Safety Data Sheet

Naste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.	
Additional information	: Flammable vapors may accumulate in the container.	
ECTION 14: Transport information		
Department of Transportation (DOT) n accordance with DOT		
Transport document description JN-No.(DOT) Proper Shipping Name (DOT) Class (DOT) Packing group (DOT) Hazard labels (DOT)	 UN1993 Flammable liquids, n.o.s., 3, II UN1993 Flammable liquids, n.o.s. 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120 II - Medium Danger 3 - Flammable liquid 	
DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) DOT Special Provisions (49 CFR 172.102)	 202 242 IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal	
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150	
DOT Quantity Limitations Passenger aircraft/rail 49 CFR 173.27)		
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L	
DOT Vessel Stowage Location	B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" or passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.	
Emergency Response Guide (ERG) Number	: 128	
Other information	: No supplementary information available.	
Transportation of Dangerous Goods		
Not applicable		
Transport by sea		
Transport document description (IMDG) JN-No. (IMDG)	: UN 1993 FLAMMABLE LIQUID, N.O.S., 3, II : 1993	
Proper Shipping Name (IMDG)	: FLAMMABLE LIQUID, N.O.S.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Class (IMDG)	: 3 - Flammable liquids			
Packing group (IMDG)	: II - substances presenting medium danger			
Limited quantities (IMDG)	: 1L			
Air transport				
Transport document description (IATA)	: UN 1993 Flammable liquid, n.o.s., 3, II			
UN-No. (IATA)	: 1993			
Proper Shipping Name (IATA)	: Flammable liquid, n.o.s.			
Class (IATA)	: 3 - Flammable Liquids			
Packing group (IATA)	: II - Medium Danger			

SECTION 15: Regulatory information

15.1. US Federal regulations

Benzene (71-43-2)					
Listed on the United States TSCA (Toxic Substan Subject to reporting requirements of United State Listed on EPA Hazardous Air Pollutant (HAPS)					
CERCLA RQ	10 lb received an adjusted RQ of 10 lbs based on potential carcinogenicity in an August 14, 1989 final rule				
Cyclohexane (110-82-7)					
Listed on the United States TSCA (Toxic Substan Subject to reporting requirements of United State					
CERCLA RQ	1000 lb				
Heparin, sodium salt (Sodium heparin, from p	oorcine intestinal mucosa) (9041-08-1)				
Listed on the United States TSCA (Toxic Substan	nces Control Act) inventory				
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).				
N-Heptane, Pure 99.0% (142-82-5)					
Listed on the United States TSCA (Toxic Substan	nces Control Act) inventory				
n-hexane (110-54-3)					
Listed on the United States TSCA (Toxic Substan Subject to reporting requirements of United State Listed on EPA Hazardous Air Pollutant (HAPS)					
CERCLA RQ	5000 lb				
Naphtha (petroleum), solvent-refined light (64	.741-84-0)				
Listed on the United States TSCA (Toxic Substan	nces Control Act) inventory				
Toluene ACS (108-88-3)					
Listed on the United States TSCA (Toxic Substan Subject to reporting requirements of United State Listed on EPA Hazardous Air Pollutant (HAPS)					
CERCLA RQ	1000 lb				
Tridodecylmethylammonium chloride (7173-5	4-8)				
Listed on the United States TSCA (Toxic Substan	nces Control Act) inventory				

15.2. International regulations

CANADA

Benzene (71-43-2)			
Listed on the Canadian DSL (Domestic Substances List)			
Toxic Substance (CEPA – Schedule I) Yes			
Cyclohexane (110-82-7)			
Listed on the Canadian DSL (Domestic Substances List)			

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Heparin, sodium salt (Sodium heparin, from porcine intestinal mucosa) (9041-08-1)
Listed on the Canadian DSL (Domestic Substances List)
N-Heptane, Pure 99.0% (142-82-5)
Listed on the Canadian DSL (Domestic Substances List)
n-hexane (110-54-3)
Listed on the Canadian DSL (Domestic Substances List)
Naphtha (petroleum), solvent-refined light (64741-84-0)
Listed on the Canadian DSL (Domestic Substances List)
Toluene ACS (108-88-3)
Listed on the Canadian DSL (Domestic Substances List)
Tridodecylmethylammonium chloride (7173-54-8)
Listed on the Canadian NDSL (Non-Domestic Substances List)

EU-Regulations

Benzene (71-43-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Benzene (71-43-2)

Listed on IARC (International Agency for Research on Cancer)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Japanese Pollutant Release and Transfer Register Law (PRTR Law)

Listed as carcinogen on NTP (National Toxicology Program)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on CICR (Turkish Inventory and Control of Chemicals)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations

Benzene (71-43-2)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	Yes	No	Yes	6.4 µg/day (oral)	24 µg/day oral

n-hexane (110-54-3)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	No	No	Yes		28000 μg/day (oral); 20,000 μg/day (inhalation)
Toluene ACS (1					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	Yes	No	No		7000 µg/day

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	State or local regulations
Benzene(71-43-2)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S Pennsylvania - RTK (Right to Know) - Special Hazardous Substances; U.S Pennsylvania - RTK (Right to Know) List
Cyclohexane(110-82-7)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
Toluene ACS(108-88-3)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
N-Heptane, Pure 99.0%(142-82-5)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
n-hexane(110-54-3)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

POLYSCIENCES, INC. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. POLYSCIENCES, INC. makes no representations or warranties, either expressed or implied of merchantability, fitness for particular purposes with respect to the information set forth herein or to which the information refers. Accordingly, POLYSCIENCES, INC. will not be responsible for damages resulting from the use of or reliance upon this information.