

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 04/14/2021 Supersedes: 02/19/2002 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Trade name : Gill's modified OG-6

Product code : 09782
Formula : no data

1.2. Recommended use and restrictions on use

Recommended use : Use as laboratory reagent, Manufacture of substances

1.3. Supplier

Supplier

Polysciences 400 Valley Road Warrington, PA 18976 - United States T +1 215 343 6484 - F +1 215 343 0214 info@polysciences.com - www.polysciences.com

1.4. Emergency telephone number

Emergency number : 24-hour emergency phone number ChemTel 1-800-255-3924

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 3 Flammable liquid and vapor

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US) : Warning

Hazard statements (GHS US) : Flammable liquid and vapor

Precautionary statements (GHS US) : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking

Keep container tightly closed.

Ground/Bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Ethyl acetate	(CAS-No.) 141-78-6	0 – 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

11/13/2023 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Methyl alcohol	(CAS-No.) 67-56-1	0 – 5	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Inhalation:vapour), H331 STOT SE 1, H370
4-methylpentan-2-one, isobutyl methyl ketone	(CAS-No.) 108-10-1	0 – 5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H335
Phosphotungstic Acid Sodium Salt	(CAS-No.) 51312-42-6	0 – 5	Eye Irrit. 2A, H319

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor.

Hazardous decomposition products in case of : Toxic fumes may be released.

fire

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

11/13/2023 EN (English US) 2/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment.

Hygiene measures

: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store at room temp. Store in a well-ventilated place. Keep cool. Keep container tightly closed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Gill's modified OG-6			
No additional information available	No additional information available		
Ethyl acetate (141-78-6)	Ethyl acetate (141-78-6)		
USA - ACGIH - Occupational Exposure Limits			
ACGIH TWA (ppm)	400 ppm		
USA - OSHA - Occupational Exposure Limits			
OSHA PEL (TWA) (mg/m³)	1400 mg/m³		
OSHA PEL (TWA) (ppm)	400 ppm		
USA - IDLH - Occupational Exposure Limits			
US IDLH (ppm)	2000 ppm (10% LEL)		
USA - NIOSH - Occupational Exposure Limits			
NIOSH REL (TWA) (mg/m³)	1400 mg/m³		
NIOSH REL TWA [ppm]	400 ppm		
Methyl alcohol (67-56-1)			
USA - ACGIH - Occupational Exposure Limits			
ACGIH TWA (ppm)	200 ppm		
ACGIH STEL (ppm)	250 ppm		
ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route		
USA - ACGIH - Biological Exposure Indices			
Biological Exposure Indices (BEI)	15 mg/l Parameter: Methanol - Medium: urine - Sampling time: end of shift (background, nonspecific)		
USA - OSHA - Occupational Exposure Limits			
OSHA PEL (TWA) (mg/m³)	260 mg/m³		
OSHA PEL (TWA) (ppm)	200 ppm		
USA - IDLH - Occupational Exposure Limits			
US IDLH (ppm)	6000 ppm		
USA - NIOSH - Occupational Exposure Limits			
NIOSH REL (TWA) (mg/m³)	260 mg/m³		
NIOSH REL TWA [ppm]	200 ppm		
NIOSH REL (STEL) (mg/m³)	325 mg/m³		
NIOSH REL STEL [ppm]	250 ppm		
US-NIOSH chemical category	Potential for dermal absorption		
4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)			
USA - ACGIH - Occupational Exposure Limits			
ACGIH TWA (ppm)	20 ppm		
ACGIH STEL (ppm)	75 ppm		
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans		
USA - ACGIH - Biological Exposure Indices			
Biological Exposure Indices (BEI)	1 mg/l Parameter: MIBK - Medium: urine - Sampling time: end of shift		

11/13/2023 EN (English US) 3/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

USA - OSHA - Occupational Exposure Limits			
OSHA PEL (TWA) (mg/m³)	410 mg/m³		
OSHA PEL (TWA) (ppm)	100 ppm		
USA - IDLH - Occupational Exposure Limits	USA - IDLH - Occupational Exposure Limits		
US IDLH (ppm)	500 ppm		
USA - NIOSH - Occupational Exposure Limits			
NIOSH REL (TWA) (mg/m³)	205 mg/m³		
NIOSH REL TWA [ppm]	50 ppm		
NIOSH REL (STEL) (mg/m³)	300 mg/m³		
NIOSH REL STEL [ppm]	75 ppm		
Phosphotungstic Acid Sodium Salt (51312-42-6)			
No additional information available			

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : orange colored liquid with organic solvent odor.

Color : Mixture contains one or more component(s) which have the following colour(s):

Colorless clear

Odor : There may be no odour warning properties, odour is subjective and inadequate to warn of

overexposure.

Mixture contains one or more component(s) which have the following odour:

Fruity alcohol-like sharp Sweet

Odor threshold : No data available pH : No data available

Melting point : no data

Freezing point : No data available

Boiling point : 173 Flash point : 51

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : Not applicable. Vapor pressure : no data

11/13/2023 EN (English US) 4/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative vapor density at 20°C : no data

Relative density : No data available Solubility No data available Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available : No data available Viscosity, kinematic Viscosity, dynamic No data available **Explosion limits** : No data available : No data available Explosive properties Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

LC50 Inhalation - Rat [ppm]

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Ethyl acetate (141-78-6)		
LD50 oral rat	5620 mg/kg	
LD50 dermal rabbit	> 18000 mg/kg	
LC50 Inhalation - Rat [ppm]	4000 ppm/4h	
Methyl alcohol (67-56-1)		
LD50 oral rat	6200 mg/kg	

4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)		
LD50 oral rat	2080 mg/kg	
LD50 dermal rabbit	3000 mg/kg	
LC50 Inhalation - Rat	8.2 mg/l/4h	

22500 ppm (Exposure time: 8 h)

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

11/13/2023 EN (English US) 5/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

Ethyl acetate (141-78-6)		
STOT-single exposure	May cause drowsiness or dizziness.	
Methyl alcohol (67-56-1)		
STOT-single exposure	Causes damage to organs.	
4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)		
STOT-single exposure	May cause respiratory irritation.	

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified Viscosity, kinematic : No data available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse

effects in the environment.

Ethyl acetate (141-78-6)		
LC50 fish 1	220 – 250 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
EC50 Daphnia 1	560 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	
LC50 fish 2	484 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])	
Methyl alcohol (67-56-1)		
LC50 fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)		
LC50 fish 1	496 – 514 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
EC50 Daphnia 1	170 mg/l (Exposure time: 48 h - Species: Daphnia magna)	

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Ethyl acetate (141-78-6)		
BCF fish 1	30	
Partition coefficient n-octanol/water (Log Pow)	0.6	
Methyl alcohol (67-56-1)		
BCF fish 1	< 10	
Partition coefficient n-octanol/water (Log Pow)	-0.77	
4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)		
Partition coefficient n-octanol/water (Log Pow)	1.19	

12.4. Mobility in soil

No additional information available

11/13/2023 EN (English US) 6/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other adverse effects

No additional information available

SECTION 13: Disposal considerations

Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1993 Flammable liquids, n.o.s., 3, II

: UN1993 UN-No.(DOT)

Proper Shipping Name (DOT) : Flammable liquids, n.o.s.

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : II - Medium Danger Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 242

: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite DOT Special Provisions (49 CFR 172.102)

(31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110

kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when

the flash point of the hazardous material transported is greater than 0 C (32 F).

TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx)

DOT Quantity Limitations Passenger aircraft/rail : 5 L

(49 CFR 173.27)

: 150

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

DOT Vessel Stowage Location

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

Emergency Response Guide (ERG) Number

Other information

: 128

: No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

Transport document description (IMDG) : UN 1993 FLAMMABLE LIQUID, N.O.S., 3, II

11/13/2023 EN (English US) 7/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

UN-No. (IMDG) : 1993

Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, N.O.S.

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : II - substances presenting medium danger

Limited quantities (IMDG) : 1 L

Air transport

Transport document description (IATA) : UN 1993 Flammable liquid, n.o.s., 3, II

UN-No. (IATA) : 1993

Proper Shipping Name (IATA) : Flammable liquid, n.o.s.

Class (IATA) : 3 - Flammable Liquids

Packing group (IATA) : II - Medium danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Ethyl acetate (141-78-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

CERCLA RQ 5000 lb

Methyl alcohol (67-56-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 5000 lb

4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 5000 lb

Phosphotungstic Acid Sodium Salt (51312-42-6)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Ethyl acetate (141-78-6)

Listed on the Canadian DSL (Domestic Substances List)

Methyl alcohol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)

Listed on the Canadian DSL (Domestic Substances List)

Phosphotungstic Acid Sodium Salt (51312-42-6)

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

EU-Regulations

Ethyl acetate (141-78-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Methyl alcohol (67-56-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

11/13/2023 EN (English US) 8/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethyl acetate (141-78-6)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Japanese Poisonous and Deleterious Substances Control Law

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on CICR (Turkish Inventory and Control of Chemicals)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

Methyl alcohol (67-56-1)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Japanese Poisonous and Deleterious Substances Control Law

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on CICR (Turkish Inventory and Control of Chemicals)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on CICR (Turkish Inventory and Control of Chemicals)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations



This product can expose you to 4-methylpentan-2-one, isobutyl methyl ketone, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Ethyl acetate(141-78-6)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S Pennsylvania - RTK (Right to Know) List
Methyl alcohol(67-56-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S Pennsylvania - RTK (Right to Know) List
4-methylpentan-2-one, isobutyl methyl ketone(108-10-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB IC)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

11/13/2023 EN (English US) 9/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS US (GHS HazCom 2012)

POLYSCIENCES, INC. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. POLYSCIENCES, INC. makes no representations or warranties, either expressed or implied of merchantability, fitness for particular purposes with respect to the information set forth herein or to which the information refers. Accordingly, POLYSCIENCES, INC. will not be responsible for damages resulting from the use of or reliance upon this information.

11/13/2023 EN (English US) 10/10