

SECTION 1: Identification

1.1. Identification

Product form	: Mixture
Trade name	: Poly-Mount Xylene
Product code	: 24176
Formula	: mixture

1.2. Recommended use and restrictions on use

Recommended use	: Use as laboratory reagent, Manufacture of substances
-----------------	--

1.3. Supplier

Supplier

Polysciences
400 Valley Road
Warrington, PA 18976 - United States
T +1 215 343 6484 - F +1 215 343 0214
info@polysciences.com - www.polysciences.com

1.4. Emergency telephone number

Emergency number	: 24-hour emergency phone number ChemTel 1-800-255-3924
------------------	---

SECTION 2: Hazard(s) identification


2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 3	Flammable liquid and vapor
Acute toxicity (oral) Category 4	Harmful if swallowed
Acute toxicity (inhalation) Category 4	Harmful if inhaled
Skin corrosion/irritation Category 2	Causes skin irritation
Serious eye damage/eye irritation Category 2B	Causes eye irritation

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)	: 
Signal word (GHS US)	: Warning
Hazard statements (GHS US)	: Flammable liquid and vapor Harmful if swallowed or if inhaled Causes skin irritation Causes eye irritation
Precautionary statements (GHS US)	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

Poly-Mount Xylene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Xylene, histology grade	(CAS-No.) 1330-20-7	31 – 40	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
Toluene	(CAS-No.) 108-88-3	31 – 40	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401
DROMETRIZOLE	(CAS-No.) 2440-22-4	0 – 5	Skin Sens. 1B, H317 Aquatic Chronic 1, H410
4-Methoxyphenol	(CAS-No.) 150-76-5	≤ 5	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 3, H402
Butyl benzyl phthalate	(CAS-No.) 85-68-7	0 – 5	Repr. 1B, H360 Aquatic Acute 1, H400 Aquatic Chronic 3, H412

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Call a poison center/doctor/physician if you feel unwell.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
- First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell. Rinse mouth.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after skin contact : Irritation.
- Symptoms/effects after eye contact : Mild eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

- Fire hazard : Flammable liquid and vapor.
- Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

Poly-Mount Xylene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store at room temp. Store in a well-ventilated place. Keep cool. Keep container tightly closed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Poly-Mount Xylene	
No additional information available	
DROMETRIZOLE (2440-22-4)	
No additional information available	
4-Methoxyphenol (150-76-5)	
USA - ACGIH - Occupational Exposure Limits	
Local name	4-Methoxyphenol
ACGIH TWA (mg/m ³)	5 mg/m ³
Remark (ACGIH)	TLV® Basis: Eye irr; skin dam
Regulatory reference	ACGIH 2020
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA) (mg/m ³)	5 mg/m ³
Butyl benzyl phthalate (85-68-7)	
No additional information available	
Toluene (108-88-3)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Toluene
ACGIH TWA (ppm)	20 ppm
Remark (ACGIH)	TLV® Basis: Visual impair; female repro; pregnancy loss. Notations: A4 (Not classifiable as a Human Carcinogen); BE1
Regulatory reference	ACGIH 2020
USA - OSHA - Occupational Exposure Limits	
Local name	Toluene
OSHA PEL (TWA) (ppm)	200 ppm
OSHA PEL C [ppm]	300 ppm
Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	500 ppm 10 mins.

Poly-Mount Xylene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Remark (OSHA)	(2) See Table Z-2.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-2
USA - IDLH - Occupational Exposure Limits	
US IDLH (ppm)	500 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA) (mg/m ³)	375 mg/m ³
NIOSH REL TWA [ppm]	100 ppm
NIOSH REL (STEL) (mg/m ³)	560 mg/m ³
NIOSH REL STEL [ppm]	150 ppm
Xylene, histology grade (1330-20-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Xylene, mixed isomers (Dimethylbenzene)
ACGIH TWA (ppm)	100 ppm
ACGIH STEL (ppm)	150 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
ACGIH chemical category	Not Classifiable as a Human Carcinogen
Regulatory reference	ACGIH 2020
USA - ACGIH - Biological Exposure Indices	
Local name	XYLENES (Technical or commercial grade)
Biological Exposure Indices (BEI)	1.5 g/g Kreatinin Parameter: Methylhippuric acids - Medium: urine - Sampling time: end of shift
Regulatory reference	ACGIH 2020
USA - OSHA - Occupational Exposure Limits	
Local name	Xylenes (o-, m-, p-isomers)
OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA PEL (TWA) (ppm)	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
 Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. [In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Poly-Mount Xylene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Appearance	: clear colorless slightly viscous liquid.
Color	: Mixture contains one or more component(s) which have the following colour(s): Colorless clear
Odor	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: caramel phenolic model airplane glue
Odor threshold	: No data available
pH	: No data available
Melting point	: no data
Freezing point	: No data available
Boiling point	: 282
Flash point	: 40
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: no data
Relative vapor density at 20°C	: no data
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Harmful if inhaled.

ATE US (oral)	500 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h

Poly-Mount Xylene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ATE US (dust, mist)	1.5 mg/l/4h
---------------------	-------------

4-Methoxyphenol (150-76-5)

LD50 oral rat	1600 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

Butyl benzyl phthalate (85-68-7)

LD50 oral rat	2330 mg/kg
LD50 dermal rat	6700 mg/kg
LD50 dermal rabbit	> 10000 mg/kg body weight Animal: rabbit
LC50 Inhalation - Rat	> 6.7 mg/l/4h

Toluene (108-88-3)

LD50 oral rat	2600 mg/kg
LD50 dermal rabbit	12000 mg/kg
LC50 Inhalation - Rat	12.5 mg/l/4h

Xylene, histology grade (1330-20-7)

LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	> 4350 mg/kg
LC50 Inhalation - Rat	29.08 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Butyl benzyl phthalate (85-68-7)

IARC group	3 - Not classifiable
National Toxicity Program (NTP) Status	Evidence of Carcinogenicity

Toluene (108-88-3)

IARC group	3 - Not classifiable
------------	----------------------

Xylene, histology grade (1330-20-7)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity	: Not classified
-----------------------	------------------

STOT-single exposure	: Not classified
----------------------	------------------

Toluene (108-88-3)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure	: Not classified
------------------------	------------------

Toluene (108-88-3)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

Xylene, histology grade (1330-20-7)

LOAEL (oral,rat,90 days)	150 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
--------------------------	--

Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Mild eye irritation.

Poly-Mount Xylene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

4-Methoxyphenol (150-76-5)	
LC50 fish 1	84.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	28.5 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
Butyl benzyl phthalate (85-68-7)	
LC50 fish 1	1.0 – 10.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	0.9 – 1.1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 fish 2	0.82 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 Daphnia 2	> 0.76 mg/l (Exposure time: 48 h - Species: Daphnia magna [Flow through])
LOEC (chronic)	1.4 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	0.2 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '124 d'
Toluene (108-88-3)	
NOEC chronic crustacea	0.74 mg/l
Xylene, histology grade (1330-20-7)	
LC50 fish 1	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 fish 2	2.661 – 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

4-Methoxyphenol (150-76-5)	
Partition coefficient n-octanol/water (Log Pow)	1.3
Butyl benzyl phthalate (85-68-7)	
BCF fish 1	187.65
Partition coefficient n-octanol/water (Log Pow)	3.57 – 4.91
Xylene, histology grade (1330-20-7)	
BCF fish 1	0.6 – 15
Partition coefficient n-octanol/water (Log Pow)	2.77 – 3.15

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapors may accumulate in the container.

Poly-Mount Xylene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1294 Toluene, 3, II
UN-No.(DOT) : UN1294
Proper Shipping Name (DOT) : Toluene
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT) : II - Medium Danger
Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
Emergency Response Guide (ERG) Number : 130
Other information : No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

Transport document description (IMDG) : UN 1294 TOLUENE, 3, II (7°C c.c.)
UN-No. (IMDG) : 1294
Proper Shipping Name (IMDG) : TOLUENE
Class (IMDG) : 3 - Flammable liquids
Packing group (IMDG) : II - substances presenting medium danger
Limited quantities (IMDG) : 1 L

Air transport

Transport document description (IATA) : UN 1294 Toluene, 3, II
UN-No. (IATA) : 1294
Proper Shipping Name (IATA) : Toluene
Class (IATA) : 3 - Flammable Liquids
Packing group (IATA) : II - Medium danger

Poly-Mount Xylene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

4-Methoxyphenol (150-76-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Butyl benzyl phthalate (85-68-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
CERCLA RQ	100 lb
Toluene (108-88-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	1000 lb
Xylene, histology grade (1330-20-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	100 lb

15.2. International regulations

CANADA

4-Methoxyphenol (150-76-5)	
Listed on the Canadian DSL (Domestic Substances List)	
Butyl benzyl phthalate (85-68-7)	
Listed on the Canadian DSL (Domestic Substances List)	
Toluene (108-88-3)	
Listed on the Canadian DSL (Domestic Substances List)	
Xylene, histology grade (1330-20-7)	
Listed on the Canadian DSL (Domestic Substances List)	

EU-Regulations

4-Methoxyphenol (150-76-5)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
Butyl benzyl phthalate (85-68-7)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
Xylene, histology grade (1330-20-7)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

National regulations

4-Methoxyphenol (150-76-5)	
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)	
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)	
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory	
Listed on the Japanese ISHL (Industrial Safety and Health Law)	
Listed on KECL/KECI (Korean Existing Chemicals Inventory)	
Listed on NZIoC (New Zealand Inventory of Chemicals)	
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)	
Listed on INSQ (Mexican National Inventory of Chemical Substances)	
Listed on CICR (Turkish Inventory and Control of Chemicals)	
Listed on the TCSI (Taiwan Chemical Substance Inventory)	

Poly-Mount Xylene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Butyl benzyl phthalate (85-68-7)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
 Listed on the Japanese ISHL (Industrial Safety and Health Law)
 Listed on KECL/KECI (Korean Existing Chemicals Inventory)
 Listed on NZIoC (New Zealand Inventory of Chemicals)
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
 Japanese Pollutant Release and Transfer Register Law (PRTR Law)
 Listed on INSQ (Mexican National Inventory of Chemical Substances)
 Listed on CICR (Turkish Inventory and Control of Chemicals)
 Listed on the TCSI (Taiwan Chemical Substance Inventory)

Xylene, histology grade (1330-20-7)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
 Listed on the Japanese ISHL (Industrial Safety and Health Law)
 Listed on KECL/KECI (Korean Existing Chemicals Inventory)
 Listed on NZIoC (New Zealand Inventory of Chemicals)
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
 Japanese Poisonous and Deleterious Substances Control Law
 Japanese Pollutant Release and Transfer Register Law (PRTR Law)
 Listed on INSQ (Mexican National Inventory of Chemical Substances)
 Listed on CICR (Turkish Inventory and Control of Chemicals)
 Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations

Butyl benzyl phthalate (85-68-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	Yes	No	No		1200 µg/day oral

Toluene (108-88-3)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	Yes	No	No		7000 µg/day

Component	State or local regulations
4-Methoxyphenol(150-76-5)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Butyl benzyl phthalate(85-68-7)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S. - Pennsylvania - RTK (Right to Know) List
Xylene, histology grade(1330-20-7)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S. - Pennsylvania - RTK (Right to Know) List
Toluene(108-88-3)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS US (GHS HazCom 2012)

Poly-Mount Xylene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

POLYSCIENCES, INC. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. POLYSCIENCES, INC. makes no representations or warranties, either expressed or implied of merchantability, fitness for particular purposes with respect to the information set forth herein or to which the information refers. Accordingly, POLYSCIENCES, INC. will not be responsible for damages resulting from the use of or reliance upon this information.