



PEG 4000 Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 05/19/2021

Supersedes: 01/12/2000

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : PEG 4000 Resin
Product code : 16861
Formula : HO-(CH₂CH₂O)_n-H

1.2. Recommended use and restrictions on use

Recommended use : Use as laboratory reagent, Manufacture of substances

1.3. Supplier

Supplier

Polysciences
400 Valley Road
Warrington, PA 18976 - United States
T +1 215 343 6484 - F +1 215 343 0214
info@polysciences.com - www.polysciences.com

1.4. Emergency telephone number

Emergency number : 24-hour emergency phone number ChemTel 1-800-255-3924

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Not classified

2.2. GHS Label elements, including precautionary statements

GHS US labeling

No labeling applicable

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Polyethylene glycol	(CAS-No.) 25322-68-3	95 – 100	STOT SE 3, H335
1,4-dioxane	(CAS-No.) 123-91-1	0 – 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H335
Acetaldehyde	(CAS-No.) 75-07-0	0 – 5	Flam. Liq. 1, H224 Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Muta. 2, H341 Carc. 1A, H350 STOT SE 3, H335 Aquatic Acute 2, H401

PEG 4000 Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Ethylene oxide	(CAS-No.) 75-21-8	0 – 5	Flam. Gas 1, H220 Press. Gas (Liq.), H280 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Inhalation:gas), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Muta. 1B, H340 Carc. 1A, H350 STOT SE 3, H335 Aquatic Acute 3, H402
Formaldehyde	(CAS-No.) 50-00-0	0 – 5	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Carc. 1A, H350 STOT SE 3, H336 Aquatic Acute 2, H401

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Specific hazards arising from the chemical

- Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Mechanically recover the product.
Other information : Dispose of materials or solid residues at an authorized site.

PEG 4000 Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store at room temp. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

PEG 4000 Resin	
No additional information available	
1,4-dioxane (123-91-1)	
USA - ACGIH - Occupational Exposure Limits	
Local name	1,4-Dioxane
ACGIH TWA (ppm)	20 ppm
Remark (ACGIH)	TLV® Basis: Liver dam. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route, Confirmed Animal Carcinogen with Unknown Relevance to Humans
Regulatory reference	ACGIH 2018
USA - OSHA - Occupational Exposure Limits	
Local name	Dioxane (Diethylene dioxide)
OSHA PEL (TWA) (mg/m ³)	360 mg/m ³
OSHA PEL (TWA) (ppm)	100 ppm
Limit value category (OSHA)	prevent or reduce skin absorption
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
US IDLH (ppm)	500 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (ceiling) (mg/m ³)	3.6 mg/m ³
NIOSH REL C [ppm]	1 ppm
Acetaldehyde (75-07-0)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Acetaldehyde
ACGIH Ceiling (ppm)	25 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: A2 (Suspected Human Carcinogen)
ACGIH chemical category	Suspected Human Carcinogen
Regulatory reference	ACGIH 2020
USA - OSHA - Occupational Exposure Limits	
Local name	Acetaldehyde
OSHA PEL (TWA) (mg/m ³)	360 mg/m ³
OSHA PEL (TWA) (ppm)	200 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
US IDLH (ppm)	2000 ppm
Ethylene oxide (75-21-8)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethylene oxide
ACGIH TWA (ppm)	1 ppm
Remark (ACGIH)	TLV® Basis: Cancer; CNS impair. Notations: A2 (Suspected Human Carcinogen)

PEG 4000 Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ACGIH chemical category	Suspected Human Carcinogen
Regulatory reference	ACGIH 2020
USA - ACGIH - Biological Exposure Indices	
Local name	ETHYLENE OXIDE
Biological Exposure Indices (BEI)	5000 pmol/g Globin Parameter: N-(2-hydroxyethyl)valine (HEV) - Medium: hemoglobin adducts - Sampling time: Not critical - Notations: Ns 5 µg/g Kreatinin Parameter: S-(2-hydroxyethyl)mercapturic acid (HEMA) - Medium: urine - Sampling time: End of shift - Notations: Pop, Ns
ACGIH remark (BEI)	The value of HEV hemoglobin adducts applies to workers having representative Ethylene oxide exposure during the previous 120 days
Regulatory reference	ACGIH 2020
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) (ppm)	1 ppm
OSHA PEL (STEL) (ppm)	5 ppm (see 29 CFR 1910.1047)
USA - IDLH - Occupational Exposure Limits	
US IDLH (ppm)	800 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA) (mg/m ³)	0.18 mg/m ³ (less than stated value)
NIOSH REL TWA [ppm]	0.1 ppm (less than stated value)
NIOSH REL (ceiling) (mg/m ³)	9 mg/m ³
NIOSH REL C [ppm]	5 ppm
Formaldehyde (50-00-0)	
No additional information available	
Polyethylene glycol (25322-68-3)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (mg/m ³)	10 mg/m ³
USA - AIHA - Occupational Exposure Limits	
WEEL TWA (mg/m ³)	10 mg/m ³ (MW>200-aerosol)

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid

PEG 4000 Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Appearance	: White solid.
Color	: Mixture contains one or more component(s) which have the following colour(s): Colorless
Odor	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: ether-like Fruity
Odor threshold	: No data available
pH	: No data available
Melting point	: 129
Freezing point	: Not applicable
Boiling point	: > ≥ 392
Flash point	: 535
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: < ≤ 0.01 mm Hg
Relative vapor density at 20°C	: > ≥ 10
Relative density	: No data available
Solubility	: Water: 67 %
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: Not applicable
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

1,4-dioxane (123-91-1)

LD50 oral rat	5170 mg/kg
LD50 dermal rabbit	7600 mg/kg

PEG 4000 Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetaldehyde (75-07-0)	
LD50 oral rat	660 mg/kg
LC50 Inhalation - Rat [ppm]	13000 ppm/4h

Ethylene oxide (75-21-8)	
LD50 oral rat	72 mg/kg
LC50 Inhalation - Rat [ppm]	800 ppm/4h

Polyethylene glycol (25322-68-3)	
LD50 oral rat	22 g/kg
LD50 dermal rabbit	> 20 g/kg
LC50 Inhalation - Rat	> 2.5 mg/l

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

1,4-dioxane (123-91-1)	
NOAEL (chronic,oral,animal/male,2 years)	94 mg/kg body weight Animal: rat, Animal sex: male, Remarks on results: other:Effect type: carcinogenicity (migrated information)
NOAEL (chronic,oral,animal/female,2 years)	148 mg/kg body weight Animal: rat, Animal sex: female, Remarks on results: other:Effect type: carcinogenicity (migrated information)
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	Reasonably anticipated to be Human Carcinogen
In OSHA Hazard Communication Carcinogen list	Yes

Acetaldehyde (75-07-0)	
IARC group	2B - Possibly carcinogenic to humans, 1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	Reasonably anticipated to be Human Carcinogen
In OSHA Hazard Communication Carcinogen list	Yes

Ethylene oxide (75-21-8)	
IARC group	1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	Known Human Carcinogens
In OSHA Hazard Communication Carcinogen list	Yes
In OSHA Specifically Regulated Carcinogen list	Yes

Formaldehyde (50-00-0)	
IARC group	1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	Known Human Carcinogens

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

1,4-dioxane (123-91-1)	
STOT-single exposure	May cause respiratory irritation.

Acetaldehyde (75-07-0)	
STOT-single exposure	May cause respiratory irritation.

Ethylene oxide (75-21-8)	
STOT-single exposure	May cause respiratory irritation.

Formaldehyde (50-00-0)	
STOT-single exposure	May cause drowsiness or dizziness.

Polyethylene glycol (25322-68-3)	
STOT-single exposure	May cause respiratory irritation.

PEG 4000 Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

STOT-repeated exposure : Not classified

1,4-dioxane (123-91-1)	
NOAEC (inhalation, rat, vapor, 90 days)	> 0.4 mg/l air Animal: rat

Aspiration hazard : Not classified

Viscosity, kinematic : No data available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

1,4-dioxane (123-91-1)	
LC50 fish 1	> 10000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	163 mg/l (Exposure time: 48 h - Species: water flea [Static])
LC50 fish 2	> 10000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [semi-static])
NOEC (chronic)	1000 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 103 mg/l Test organisms (species): Pimephales promelas Duration: '32 d'

Acetaldehyde (75-07-0)	
LC50 fish 1	28.0 – 34.0 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	3.64 – 6.15 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 fish 2	53 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 2	48.3 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Ethylene oxide (75-21-8)	
LC50 fish 1	73 – 96 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 Daphnia 1	137 – 300 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

1,4-dioxane (123-91-1)	
BCF fish 1	0.2 – 0.7
Partition coefficient n-octanol/water (Log Pow)	-0.42

Acetaldehyde (75-07-0)	
Partition coefficient n-octanol/water (Log Pow)	0.5

Ethylene oxide (75-21-8)	
Partition coefficient n-octanol/water (Log Pow)	-0.3 (at 25 °C)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

PEG 4000 Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not applicable

Transportation of Dangerous Goods

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

1,4-dioxane (123-91-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313
Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	100 lb
-----------	--------

Acetaldehyde (75-07-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313
Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	1000 lb
-----------	---------

Ethylene oxide (75-21-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313
Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	10 lb
RQ (Reportable quantity, section 304 of EPA's List of Lists)	10 lb
Section 302 EPCRA Reportable Quantity (RQ)	10 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb

Formaldehyde (50-00-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313
Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	100 lb
RQ (Reportable quantity, section 304 of EPA's List of Lists)	100 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	500 lb

Polyethylene glycol (25322-68-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
--------------------------	---

15.2. International regulations

CANADA

PEG 4000 Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,4-dioxane (123-91-1)	
Listed on the Canadian DSL (Domestic Substances List)	
Acetaldehyde (75-07-0)	
Listed on the Canadian DSL (Domestic Substances List)	
Toxic Substance (CEPA – Schedule I)	Yes
Ethylene oxide (75-21-8)	
Listed on the Canadian DSL (Domestic Substances List)	
Toxic Substance (CEPA – Schedule I)	Yes
Formaldehyde (50-00-0)	
Listed on the Canadian DSL (Domestic Substances List)	
Polyethylene glycol (25322-68-3)	
Listed on the Canadian DSL (Domestic Substances List)	

EU-Regulations

Ethylene oxide (75-21-8)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

1,4-dioxane (123-91-1)
Listed on IARC (International Agency for Research on Cancer) Listed as carcinogen on NTP (National Toxicology Program)
Acetaldehyde (75-07-0)
Listed as carcinogen on NTP (National Toxicology Program)
Ethylene oxide (75-21-8)
Listed on IARC (International Agency for Research on Cancer) Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Japanese ISHL (Industrial Safety and Health Law) Listed on KECL/KECI (Korean Existing Chemicals Inventory) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Japanese Poisonous and Deleterious Substances Control Law Japanese Pollutant Release and Transfer Register Law (PRTR Law) Listed as carcinogen on NTP (National Toxicology Program) Listed on INSQ (Mexican National Inventory of Chemical Substances) Listed on CICR (Turkish Inventory and Control of Chemicals) Listed on the TCSI (Taiwan Chemical Substance Inventory)
Formaldehyde (50-00-0)
Listed on IARC (International Agency for Research on Cancer) Listed as carcinogen on NTP (National Toxicology Program)

15.3. US State regulations

1,4-dioxane (123-91-1)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No	30 µg/day	
Acetaldehyde (75-07-0)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No	90 µg/day (inhalation)	

PEG 4000 Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethylene oxide (75-21-8)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	Yes	Yes	Yes	2 µg/day	20 µg/day
Formaldehyde (50-00-0)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No	40 µg/day	

Component	State or local regulations
1,4-dioxane(123-91-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Acetaldehyde(75-07-0)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Ethylene oxide(75-21-8)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances; U.S. - Pennsylvania - RTK (Right to Know) List
Formaldehyde(50-00-0)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS US (GHS HazCom 2012)

POLYSCIENCES, INC. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. POLYSCIENCES, INC. makes no representations or warranties, either expressed or implied of merchantability, fitness for particular purposes with respect to the information set forth herein or to which the information refers. Accordingly, POLYSCIENCES, INC. will not be responsible for damages resulting from the use of or reliance upon this information.