

U.S. Corporate Headquarters 400 Valley Rd. Warrington, PA 18976 1(800) 523-2575 / (215) 343-6484 1(800)343-3291 fax info@polysciences.com Polysciences Europe GmbH Badener Str. 13 69493 Hirschberg an der Bergstrasse, Germany +(49) 06201-845200 +(49) 06201-8452020 fax info@polysciences.de Polysciences Asia-Pacific, Inc. 2F-1, 207 DunHua N. Rd. Taipei, Taiwan 10595 (886) 2 8712 0600 (886) 2 8712 2677 fax info@polysciences.tw

TECHNICAL DATA SHEET 508

Page 1 of 2

Flow Check[™] Microparticles

DESCRIPTION

Flow Check[™] beads have been designed to assist flow cytometry users in checking the suitability of their instruments and their procedures. The particles are made from a polystyrene base and supplied as an aqueous suspension. All components are packaged in convenient 10ml flip-top dropper bottles. To reach a count rate of 1000 per second, a dilution is required. With 10,000 total events per run, a single bottle of Flow Check[™] particles can be used for at least 200 runs. When protected from light and stored at 4°C, the particles will be stable for one year.

Dyed Particle	Excitation Max. (nm)	Emission Max. (nm)
BB	365	435
YG	445	500
Ruby Red	475	663

AVAILABLE PRODUCTS

Flow Check™ High Intensity Alignment Grade Particles -0.50µm (BB) (Cat. # 23520-1)

These are a single popultion of 0.50µm polystyrene particles that can be used for flow cytometry calibration. The fluorescence emission is in the range of 360nm to 407nm.


Flow Check™ YG 6.0µm Kit (Cat. #23512-1)

The particles in this kit allow comparison of various levels of green fluorescence on uniform polystyrene beads. A full intensity bead, two intermediate intensity beads, and a blank bead are provided to assist in checking instrument stability in the appropriate ranges. Each component is packaged with ~2 x 10^6 particles per ml. The CV's of these particles are narrow throughout the range.

Flow Check™ 6.0µm Ruby Red Microspheres (Cat. #24288-5)

These microspheres are 6µm narrow distribution polystyrene particles that can be used for flow cytometry applications with red excitation and

fluorescence emission in the range of 600nm to 710nm are needed. Particles are supplied at an approximate concentration of 5 x 10^6 microspheres per ml in a convenient dropper bottle.



ADDITIONAL PRODUCTS

Additional products designed for use in flow cytometry applications can be found in the Microspheres section under *Bangs Flow Cytometry Standards* on our website, **www.polysciences.com**.

STORAGE

Store Flow Check^M Flow Cytometry particle suspensions at 4°C when not in use. Prior to dispensing, particles should be well mixed by completely inverting the bottle several times. For use, dilute one drop of the particle suspension in 1ml of sheath fluid and mix well. Diluted particles should be stored at 4°C and protected from light. Diluted particles are stable for 8-10 hours when stored in the dark at 4°C.

These products are for research use only and are not intended for use in humans or for *in vitro* diagnostic use.

ORDERING INFORMATION

Cat. #	Description	Size
23520-1	Flow Check [™] High Intensity Alignment Grade 0.5µm (BB)	10ml
23512-1	Flow Check [™] YG 6.0µm Kit	1 kit
23519-10	Flow Check [™] YG 6.0µm High Intensity	10ml
23522-10	Flow Check [™] YG 6.0µm Low Intensity Level 1	10ml
23523-10	Flow Check [™] YG 6.0µm Low Intensity Level 2	10ml
23521-10	Flow Check [™] YG 6.0µm Unlabeled	10ml
23518-10	Flow Check [™] YG 2.0µm High Intensity	10ml
24288-5	Flow Check [™] Ruby Red Fluorescent Microspheres	5ml

TO ORDER

In The U.S. Call:	1(800) 523-2575 • (215) 343-6484
In The U.S. Fax:	1(800) 343-3291 • (215) 343-0214
In Germany Call:	+(49) 06201-845200
In Germany Fax:	+(49) 06201-8452020
In Asia Call:	(886) 2 8712 0600
In Asia Fax:	(886) 2 8712 2677

Order online anytime at www.polysciences.com

Should any of our materials fail to perform to our specifications, we will be pleased to provide replacements or return the purchase price. We solicit your inquiries concerning all needs for life sciences work. The information given in this bulletin is to the best of our knowledge accurate, but no warranty is expressed or implied. It is the user's responsibility to determine the suitability for their own use of the products described herein, and since conditions of use are beyond our control, we disclaim all liability with respect to the use of any material supplied by us. Nothing contained herein shall be construed as a recommendation to use any product or to practice any process in violation of any law or any government regulation.